



[www.rhopointinstruments.com](http://www.rhopointinstruments.com)

## VISCOSITY FLOW CUPS

**RHOPOINT**  
**PAINTLAB+ ©**

- Precise flow rate measurement
- Choice of standards of compliance
- Robust design and construction



Rhopoint Instruments Limited  
is a member of the  
Rhopoint Group

# VISCOSITY FLOW CUPS

The Rhopoint *PAINTLAB+* Flow Cups are designed to accurately measure the viscosity of paints, inks, varnishes and similar products.





The process of flow through an orifice can often be used as a relative measurement and classification of viscosity.

This measured kinematic viscosity is generally expressed in seconds of flow time which can be converted into centistokes (cSt) using a viscosity calculator.

Manufactured from high grade aluminium alloy with stainless steel orifices (where indicated), the Rhopoint *PAINTLAB+* Flow Cups are available with a range of UKAS / ISO 17025 certified standard oils to confirm the flow cup is measuring within specification.



**VISCOSITY FLOW CUPS**

Product	Order code	Orifice diameter	Viscosity range	Flow times
 <p><b>BS FLOW CUP</b> BS 3900 (1971) Old Specification (B2) BS 3900 (1971) Old Specification (B3) BS 3900 (1971) Old Specification (B4) BS 3900 (1971) Old Specification (B5) BS 3900 (1971) Old Specification (B6)</p>	RL-A-FC-PTA6/B2	2.38mm (0.09")	38 - 71cSt	} 30 - 300 secs
	RL-A-FC-PTA6/B3	3.17mm (0.12")	38 - 147cSt	
	RL-A-FC-PTA6/B4	3.97mm (0.16")	71 - 455cSt	
	RL-A-FC-PTA6/B5	4.76mm (0.19")	299 - 781cSt	
	RL-A-FC-PTA6/B6	7.14mm (0.28")	781 - 1650cSt	
 <p><b>DIN FLOW CUP</b> Din Flow Cup (2mm) - Din 53211 Din Flow Cup (4mm) - Din 53211 Din Flow Cup (6mm) - Din 53211 Din Flow Cup (8mm) - Din 53211 The orifices are manufactured from stainless steel.</p>	RL-A-FC-DIN2	2mm (0.08")	15 - 30cSt	} 25 - 150 secs
	RL-A-FC-DIN4	4mm (0.16")	112 - 685cSt	
	RL-A-FC-DIN6	6mm (0.24")	550 - 1500cSt	
	RL-A-FC-DIN8	8mm (0.31")	1200 - 3000cSt (approximately)	
 <p><b>FORD FLOW CUP</b> Ford Flow Cup No 1 - ASTM D1200 Ford Flow Cup No 2 - ASTM D1200 Ford Flow Cup No 3 - ASTM D1200 Ford Flow Cup No 4 - ASTM D1200 Ford Flow Cup No 5 - ASTM D1200 The orifices are manufactured from stainless steel.</p>	RL-A-FC-ASTM1	2.1mm (0.08")	10 - 35cSt	} 55 - 100 secs 40 - 100 secs 30 - 100 secs 30 - 100 secs 30 - 100 secs
	RL-A-FC-ASTM2	2.8mm (0.11")	25 - 120cSt	
	RL-A-FC-ASTM3	3.4mm (0.13")	49 - 220cSt	
	RL-A-FC-ASTM4	4.1mm (0.16")	70 - 370cSt	
	RL-A-FC-ASTM5	5.8mm (0.23")	200 - 1200cSt	
 <p><b>ISO/ASTM FLOW CUP</b> Flow Cups to BS EN ISO 2431, ASTM D5125 Flow Cups to BS EN ISO 2431, ASTM D5125 Flow Cups to BS EN ISO 2431, ASTM D5125 Flow Cups to BS EN ISO 2431, ASTM D5125 Flow Cups to BS EN ISO 2431, ASTM D5125 The orifices are manufactured from stainless steel.</p>	RL-A-FC-ISO3	3mm (0.12")	7 - 42cSt	} 30 - 100 secs
	RL-A-FC-ISO4	4mm (0.16")	35 - 135cSt	
	RL-A-FC-ISO5	5mm (0.20")	91 - 325cSt	
	RL-A-FC-ISO6	6mm (0.24")	188 - 684cSt	
	RL-A-FC-ISO8	8mm (0.31")	600 - 2000cSt	
 <p><b>AFNOR FLOW CUP</b> Afnor Flow Cup - 2.5mm - NF T30-014 Afnor Flow Cup - 4mm - NF T30-014 Afnor Flow Cup - 6mm - NF T30-014 Afnor Flow Cup - 8mm - NF T30-014</p>	RL-A-FC-AFNOR/2.5	2.5mm (0.10")	5 - 140cSt	} 30 - 100 secs
	RL-A-FC-AFNOR/4	4mm (0.16")	50 - 1100cSt	
	RL-A-FC-AFNOR/6	6mm (0.24")	510 - 5100cSt	
	RL-A-FC-AFNOR/8	8mm (0.31")	700 - 11500cSt	
 <p><b>FRIKMAR FLOW CUP</b> Frikmar Flow Cup 2mm Frikmar Flow Cup 4mm Frikmar Flow Cup 6mm Frikmar Flow Cup 8mm The orifices are manufactured from stainless steel.</p>	RL-A-FC-FRIKMAR/2	2mm (0.08")	15 - 30 cSt	} 25 - 150 secs
	RL-A-FC-FRIKMAR/4	4mm (0.16")	112 - 685cSt	
	RL-A-FC-FRIKMAR/6	6mm (0.24")	550 - 1500cSt	
	RL-A-FC-FRIKMAR/8	8mm (0.31")	1200 - 3000cSt (approximately)	



# VISCOSITY FLOW CUPS

## SPECIFICATION

- **Material:** High grade aluminium alloy
- **Commodity Code:** 9027 8091
- **Weight:** 200 - 300g depending on model

## CALIBRATION OILS

Order Code	Nominal Value 25°C (cSt)
RL-A-VISCOSITYOIL 14	17
RL-A-VISCOSITYOIL 28	33
RL-A-VISCOSITYOIL 50	59
RL-A-VISCOSITYOIL 75	88
RL-A-VISCOSITYOIL 100	115
RL-A-VISCOSITYOIL 150	174
RL-A-VISCOSITYOIL 200	233
RL-A-VISCOSITYOIL 250	289
RL-A-VISCOSITYOIL 300	352
RL-A-VISCOSITYOIL 350	405
RL-A-VISCOSITYOIL 390	446
RL-A-VISCOSITYOIL 500	580
RL-A-VISCOSITYOIL 750	862
RL-A-VISCOSITYOIL 1000	1160
RL-A-VISCOSITYOIL 1500	1718
RL-A-VISCOSITYOIL 2500	2860
RL-A-VISCOSITYOIL 3900	4530
RL-A-VISCOSITYOIL 6000	6900
RL-A-VISCOSITYOIL 7750	9000
RL-A-VISCOSITYOIL 10000	11300
RL-A-VISCOSITYOIL 15000	17000
RL-A-VISCOSITYOIL 20000	22500



## ACCESSORIES

- Certificate of conformity (included)

## OPTIONAL EXTRAS


- UKAS / ISO 17025 calibration certificate
- **Flow cup stand** – Lightweight aluminium stand suitable for use with all Rhopoint flow cups. Supplied with spirit level.



Certificate no: FM 29741  
ISO 9001:2008



LOCAL AGENT



00307/12/13