

## Digital coating thickness gauges SAUTER TF · TG

PREMIUM  
★★★★



SAUTER TF



PREMIUM  
★★★★



SAUTER TG

Premium coating thickness gauge for paint coating, lacquer coating etc.

Features	Technical data	Accessories
----------	----------------	-------------

- **LCD display**, backlit, display of all information at a glance
- **Offset-Accur**: This function allows you to adjust the instrument precisely on the locally measured range by a two-point calibration. This results in a superior accuracy of approx. 1 % of the measured value
- **Scan mode** for continuous measurement or single point measuring mode
- **Mini Statistics Kit**: displays the measured result, the average value and the max and the min value
- **Internal memory** up to 99 values
- **Selectable measuring units**: μm, mil
- **Base plate and calibration foils** included
- **Data interface RS-232** standard
- **Delivered in a robust carrying case**, figure shows SAUTER TF


- **Measuring precision**:
  - Standard: 3 % of measured value or ± 2,5 μm
  - Offset-Accur: 1 % of measured value or ± 1 μm
- **Minimum thickness of base material**: 300 μm
- **Dimensions W×D×H** 65×35×126 mm
- **Battery operation**, batteries standard 2× 1.5 V AAA
- **Net weight** approx. 81 g

- **Data transfer software**, interface cable included, SAUTER ATC-01
- **Calibration foils** for increased measuring accuracy (covers the range from 20 up to 2000 μm, with < 3 % tolerance), SAUTER ATB-US07
- SAUTER TG: **External sensor**, TypeFN, SAUTER ATG 01

**SAUTER TG:**

- **External sensor** for difficult-to-access measuring points

STANDARD





































OPTION



Model	Measuring range [Max] μm	Readout [d] μm	Test object	Smallest sample surface (radius) mm	Option Factory calibration certificates	
					KERN	
SAUTER TF 1250-0.1FN.	100   1250	0,1   1	Combination instrument: F/N	F: Convex: 1,5 Concave: 25	961-112	
SAUTER TG 1250-0.1FN.	100   1250	0,1   1	Combination instrument: F/N	N: Convex: 3 Concave: 50	961-112	

## Pictograms

 <b>Adjusting program (CAL):</b> For quick setting of the instrument's accuracy. External adjusting weight required.	 <b>Control outputs (optocoupler, digital I/O):</b> to connect relays, signal lamps, valves, etc.	 <b>ZERO:</b> Resets the display to "0".
 <b>Calibration block:</b> standard for adjusting or correcting the measuring device.	 <b>Analogue interface:</b> to connect a suitable peripheral device for analogue processing of the measurements	 <b>Battery operation:</b> Ready for battery operation. The battery type is specified for each device.
 <b>Peak hold function:</b> capturing a peak value within a measuring process.	 <b>Statistics:</b> using the saved values, the device calculates statistical data, such as average value, standard deviation etc.	 <b>Rechargeable battery pack:</b> rechargeable set.
 <b>Scan mode:</b> continuous capture and display of measurements.	 <b>PC Software:</b> to transfer the measurement data from the device to a PC.	 <b>Mains adapter:</b> 230V/50Hz in standard version for EU. On request GB, AUS or USA version available.
 <b>Push and Pull:</b> the measuring device can capture tension and compression forces.	 <b>Printer:</b> a printer can be connected to the device to print out the measurement data.	 <b>Power supply:</b> Integrated, 230V/50Hz in EU. More standards e.g. GB, AUS or USA on request.
 <b>Length measurement:</b> captures the geometric dimensions of a test object or the movement during a test process.	 <b>Network interface:</b> For connecting the scale to an Ethernet network.	 <b>Motorised drive:</b> The mechanical movement is carried out by a electric motor.
 <b>Focus function:</b> increases the measuring accuracy of a device within a defined measuring range.	 <b>KERN Communication Protocol (KCP):</b> It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems.	 <b>Motorised drive:</b> The mechanical movement is carried out by a synchronous motor (stepper).
 <b>Internal memory:</b> to save measurements in the device memory.		 <b>Fast-Move:</b> the total length of travel can be covered by a single lever movement.
 <b>Data interface RS-232:</b> bidirectional, for connection of printer and PC.	 <b>GLP/ISO record keeping:</b> of measurement data with date, time and serial number. Only with SAUTER printers	 <b>DAkkS calibration possible:</b> The time required for DAkkS calibration is shown in days in the pictogram.
 <b>Data interface USB:</b> To connect the measuring instrument to a printer, PC or other peripheral devices.	 <b>Measuring units:</b> Weighing units can be switched to e.g. non-metric at the touch of a key. Please refer to website for more details.	 <b>Factory calibration:</b> The time required for factory calibration is specified in the pictogram.
 <b>WLAN data interface:</b> To transfer data from the balance to a printer, PC or other peripherals.	 <b>Measuring with tolerance range (limit-setting function):</b> Upper and lower limiting can be programmed individually. The process is supported by an audible or visual signal, see the relevant model	 <b>Package shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram.
 <b>Data interface Infrared:</b> To transfer data from the measuring instrument to a printer, PC or other peripheral devices.		 <b>Pallet shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram.

Your KERN specialist dealer: